



## **OBS 18 & 18DC** Orbital Sanders

- **Powerful fully-enclosed motor**
- **Rigid cast aluminum pad driver**
- **Fine finishes hardwood floors**
- **Large non-marking wheels**
- **Precision-balanced**

The random-orbital sanding action of the OBS 18 and OBS 18DC removes the scratch patterns left by drum or rotary sanders, leaving a smooth, flat floor ready for refinishing.

The OBS 18 and OBS 18DC are perfect for interim “screen and recoat” sanding jobs.



The dust skirt assembly for the OBS 18DC model helps prevent airborne dust.

**Because Pride Still Matters.**

**A Nilfisk-Advance Brand**

**Clarke®**  
**American Sanders**



SPECIFICATIONS	OBS 18	OBS 18DC
Part Number	07076B	07081B
Sanding Path	18 in	
Sanding Pad Size	12 in x 18 in	
Motor	1 hp	
Voltage	115 V / 60 Hz	
Power Cable	50 ft 14-3 grey	
Sanding Pad Speed (AC)	3,600 orbits per minute	
Sound Level	74 dB A	
Dimensions	18 in x 20 in x 45 in	
Weight	125 lb	
Warranty	Parts and Labor - 1 Year	

Specifications are subject to change without notice.

#### What enhances its productivity?

- Powerful fully-enclosed motor
- Heavy frame for aggressive sanding
- Operates in any direction
- Provides even, consistent performance

#### What are the safety features?

- DC model controls airborne dust
- Hospital grade plug assures electrical safety when connected to a properly grounded outlet

#### What are the accessories?

- Extra sandpaper
- Quick-release dust bags
- Dust skirt assembly



recyclable

14600 21st Avenue North • Plymouth, MN 55447-3408  
Phone: 800.253.0367 • Fax: 800.825.2753

240 Superior Boulevard • Mississauga, Ontario, Canada L5T 2L2  
Phone: 800.668.8400 • Fax: 800.263.5111

©2009 Nilfisk-Advance, Inc. All rights reserved. P/N 79703A 8/09

**Clarke<sup>®</sup>**  
**American Sanders**