



2000 - 3000 sq.ft./gallon

BETCO[®] MATTE FINISH



Low Gloss Floor Finish

This floor finish was specifically designed for facilities which require a protective coating on floors but prefer a low gloss appearance. It is a durable, low maintenance finish which is easy to apply and maintain. The low gloss appearance makes this finish perfect for use in healthcare facilities.

Uses

- Resilient tile
- Terrazzo
- Linoleum
- Commercial sheet vinyl

Features

- Low gloss.
- Extended wear formula.
- Self Sealing.
- Excellent leveling.

Properties

Color (dried).....	Crystal Clear
Color (liquid)	White
Coverage.....	2000 - 3000 square feet/gallon
Drying time	30 - 40 minutes per coat
Fragrance	Mild
Freeze/thaw stability	3 cycles
Gloss (ASTM D 1455)	One coat 30 - 35 Two coats 35 - 40
Heel mark resistance	Very good
Leveling	Excellent
pH	7.0 - 8.5
Powdering resistance	Excellent
Recoat	Very Good
Specific Gravity.....	1.06
Free styrene content	0.0
Shelf life.....	1 year

Directions For Use

Read the entire label before using this product.

RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. 3 - 4 coats of finish are recommended. **Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a sealer will extend the long term performance.**

ROUTINE MAINTENANCE: Sweep large debris and dust mop (using a water based treatment). Damp mop or automatic scrub using a neutral pH cleaner. INTERIM MAINTENANCE: Sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. **Note: Slip resistance meets or exceeds (ASTM D 2047-93) James Machine 0.5 minimum.**

Safety

Keep out of reach of children. For institutional and commercial use only. **CAUTION:** Eye irritant. May cause skin irritation. May cause respiratory irritation. Harmful if swallowed. **FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. If swallowed, drink two glasses of water. Call a physician. If inhaled, remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration, preferably mouth-to-mouth.

Available In

Case/4 - 1 Gallon (3.78L): Item #66504-00

Literature Item #66592-92

